


7.901.103 / 13.901.151

Turbine Spray Gun Long Range Spray Gun

Maximum Flow 25.0 / 30.0 GPM / 95 / 114 lpm
Maximum Pressure 850 PSI / 58 bar



Revised 6-17-2025

Part #	Description	Qty
1238.86	Washer	1
1238.87	Inlet Adapter	1
1238.60	Handle	1
1238.78	Inlet Tube	1
1603.83	Plug	1
1101.D4	O-Ring ■	1
1238.A4	Spring	1
0205.17	Poppet ■	1
009	Seat ■ (Kit Only)	1
010	Body (Not Replaceable)	1
011	O-Ring ■ (Kit Only)	1
1238.89	Plunger	1
1101.76	O-Ring ■	1
1238.A5	Guide	1
1238.A2	Trigger	1
1240.F4	Trigger Clip	1
1238.77	Trigger Pin	1

Part #	Description	Qty
1238.90	Washer	1
1238.88	Nut	1
1240.V5	Front Handle	1
1241.N7	Front Grip	1
1805.58	Bolt	2
1403.30	Washer	2
1101.06	O-Ring ■	2
1209.40	Regulator	1
029	Inner Tube (Not Replaceable)	1
029/LR	Inner Tube - Long Range (Not Replaceable)	1
1240.04	Nozzle Protector	1
1238.A7	Nozzle Protector - Long Range	1
1238.96	Nozzle Retainer	1
1238.A6	Nozzle Retainer - Long Range	1
1101.D5	O-Ring ■	1

■ Parts Included in Repair Kit #8711.01

Spray Tip Performance Chart

Model	Orifice (mm)	Material	Gallons per Minute / Maximum Spray Distance in Feet				
			100 PSI	200 PSI	400 PSI	600 PSI	800 PSI
1701.30	1.5	Ceramic	.78 / 17	1.1 / 20	1.5 / 23	1.8 / 25	2.1 / 27
1701.53	1.8	Ceramic	1.1 / 19	1.6 / 21	2.3 / 24	2.6 / 26	2.9 / 28
1701.31	2.0	Ceramic	1.4 / 21	2.0 / 24	2.8 / 26	3.4 / 29	3.8 / 32
1701.32	2.3	Ceramic	2.0 / 24	2.5 / 29	4.0 / 34	5.0 / 42	5.5 / 45
1701.33	2.5	Ceramic	2.5 / 23	3.0 / 28	4.5 / 32	5.5 / 40	6.5 / 44
1701.26	3.0	Ceramic	3.0 / 28	4.5 / 29	6.5 / 34	8.0 / 41	9.0 / 44
1701.45	3.5	S/S	4.5 / 31	6.0 / 36	8.5 / 41	11.0 / 50	12.0 / 54
1701.34	4.0	S/S	5.0 / 35	7.5 / 38	10.0 / 43	13.5 / 53	14.5 / 59
1701.46	4.5	S/S	6.5 / 37	9.0 / 39	12.5 / 44	16.5 / 54	18.0 / 62
1701.44	5.0	S/S	7.5 / 33	10.0 / 41	14.0 / 47	18.5 / 59	21.0 / 67
1701.47	5.5	S/S	8.0 / 35	11.5 / 42	16.0 / 47	21.0 / 59	23.0 / 70
1701.48	6.0	S/S	9.0 / 38	12.5 / 44	18.0 / 54	23.0 / 66	26.0 / 74
1701.43	7.0	S/S	9.5 / 21	13.5 / 47	19.0 / 57	24.0 / 70	27.0 / 77