

143 LBS
128 OZ UDOR LUBE

***Dimensional Drawings are
Shown in Millimeters.
To Convert to Inches,
Multiply Dimension x 0.03937***

Technical drawing of the 3000 series hydraulic pump, showing front and side views with dimensions in millimeters (mm) and inches (in).

Front View Dimensions:

- Overall width: 421 mm
- Overall height: 100 mm
- Top flange width: 30 mm
- Top flange height: 20 mm
- Top flange offset: 10 mm
- Top flange diameter: $\varnothing 122$
- Top flange thread: G1/4"
- Top flange offset: 216 mm
- Top flange offset: 66 mm
- Top flange offset: 342 mm
- Top flange offset: 32 mm
- Top flange offset: 35 mm
- Top flange offset: 55 mm
- Top flange offset: 140 mm
- Top flange offset: 195 mm
- Top flange offset: 140 mm
- Top flange offset: 421 mm

Side View Dimensions:

- Overall width: 397 mm
- Overall height: 229 mm
- Top flange width: 123 mm
- Top flange height: 75 mm
- Top flange offset: 75 mm
- Top flange offset: 5 mm
- Top flange offset: 91 mm
- Top flange offset: 80 mm
- Top flange offset: 70 mm
- Top flange offset: 5 mm
- Top flange offset: 12 mm
- Top flange offset: 43 mm
- Top flange offset: 30 mm
- Top flange offset: 44.5 mm
- Top flange offset: 157 mm
- Top flange offset: 240 mm
- Top flange offset: 397 mm

Other Dimensions:

- Top flange thread: G3/8" oil drain plug
- Top flange thread: N.6 M14
- Top flange thread: M12
- Top flange thread: $\varnothing 40$ k6
- Top flange thread: $\varnothing 95.5^{+0.04}_0$